



Armor Guard Protector

Extreme Performance Coating

All Floors All the Shine



DIRECTIONS

Armor Guard Floor Protector is an Extreme Performance Floor Coating that produces Rapid Shine Development with never before seen Abrasion and Stain Protection. Armor Guard Floor Protector utilizes proprietary Nano-Particulate Xpolymer Technology (NPXT) to produce a surface that is up to 6 times more resistant to abrasion & wear than traditional floor finishes.

FLOOR PREPARATION

- For best results strip the floor of all existing finish or coatings. Strip even new/factory installed floors of their factory finish. Be careful to remove all floor finish as any remaining finish has potential to be visible after applying Armor Guard Floor Protector.
- Dust mop to ensure the floor is clean and free of all grit & particles prior to Armor Guard application.
- If stains are present they should be thoroughly cleaned.
- Always rinse the floor well after stripping. Failure to properly rinse a floor can prevent Armor Guard Floor Protector from adhering to the floor properly, discoloration, hazing, or other failures.

Application Procedure:

1. For best results burnish entire floor using a Sidewinder 1500 or 3000 Grit Floor Pad. This step dramatically improves resulting gloss.
2. Apply a pool of product to the floor and using a clean micro-fiber pad and applicator, apply at a rate of 2,500-3000 sq. ft. per gallon. (coverage will depend on surface profile) Spread material thinly and evenly so as to completely cover the substrate. Make sure that all drips or heavy areas are addressed while applying. Proper coating thickness should NOT have any milky appearance to it. Treat the application almost like you are applying product and then trying to wipe it off.
3. When application is complete allow time to fully dry. (20-30 mins) The more porous the flooring the longer it will take for product soaked into the floor to fully dry.
4. Wait a minimum of 15 minutes after floor is dry to the touch to move on to next step.
5. Apply second thin even coat of Armor Guard Floor Protector.
6. After a period of 24 hours burnish for a minimum of 5 passes using a Stone-Glo Sidewinder 1500 or 3000 Grit Floor Pad. Efforts should be made to burnish the floor at least 4 times within the first month. This additional burnishing will assist in long term durability and soil resistance.

ONGOING MAINTENANCE

- Dust mop.
- Damp mop or auto scrub as necessary using Neutral Ph Cleaner.
- Flooring should be periodically burnished (typically 1-2 times per week) using Stone-Glo Sidewinder floor pads to maintain gloss. When traffic lanes are no longer returned to gloss by burnishing an application of Armor-Guard Floor Protector should be applied.
- Recoat traffic areas or entire floors with Armor-Guard Protector. Be sure the floor is clean and free of marks before recoating.

ADVANTAGES

- Not a finish – hybrid polymer protective coating
- 6X more resistant to abrasion & wear
- Develops initial hardness 40% faster than traditional floor finish, reduces risk of early damage
- Imparts high gloss reflectivity when burnished
- Superior clarity, will not peel, flake or fade
- Easy to maintain & spot repair, reapply-chemically bonds
- Heavy duty protection against stains
- Easy-to-use, water-based formula
- Low odor, VOC compliant, environmentally friendly
- Maybe be used as a top coat – compatible with traditional floor finishes.

HEALTH AND SAFETY PRECAUTIONS:

KEEP OUT OF THE REACH OF CHILDREN. Do not take internally. Avoid prolonged contact with skin. Avoid ingestion of material. If swallowed, do not induce vomiting- call physician. Avoid contact with eyes. Protective clothing is recommended. Protective goggles are recommended in case of splashing. If splashed in eyes, wash immediately with clean water and call physician if irritation persists. Contact areas should be thoroughly washed with soap and water. Additional precautions, safety information and first aid treatments are contained in the Safety Data Sheets. ARMOR GUARD will bond to most surfaces- immediately wash off or spray with water and mild detergent. CAUTION: Surfaces wet with ARMOR GUARD may be slippery.

PROFESSIONAL USE ONLY
KEEP OUT OF REACH OF CHILDREN

All Floors All the Shine

