

SHELD PROPERTY.

All Floors All the Shine

Floormance Floormance Floormance Floormance

ULTRA SHIELD HIGH PERFORMANCE FLOOR FINISH is an extended performance high solids floor finish which contains a unique additive that gives it superior gloss and excellent durability. **ULTRA SHIELD FLOOR FINISH** requires no buffing, but is well suited to a high speed spray buff system.

DIRECTIONS FOR USE

INITIAL APPLICATION: For best results remove all old wax and polish. Rinse thoroughly after removing residue with clear water. When the floor is completely dry, apply **ULTRA SHIELD FLOOR FINISH** with a nylon mop or wax applicator. Allow to dry completely before a second coat is applied. Buffing is not considered necessary until after the floor has been exposed to regular traffic.

MAINTENANCE: Periodic sweeping, dust mopping, and damp mopping with a neutral cleaner will considerably extend the life of the finish. Spray buff or burnish as necessary. Worn or dirty areas may be spot cleaned and spot coated without redoing the entire floor.

CAUTION: Avoid eye contact and prolonged contact with skin. Do not take internally. Wear protective gloves and protective goggles when handling.

FIRST AID: If swallowed, DO NOT induce vomiting. Give large quantities of water. Call a physician immediately. Never give anything by mouth to an unconscious person. In case of contact with eyes or skin, flush with plenty of water for at least 15 minutes. Call a physician if irritation persists.

INGREDIENTS: Water (CAS#7732-18-5), Acrylic Copolymer (CAS# 62180-77-2), Diethylene Glycol Monomethyl Ether (CAS# 111-773), Polyethylene Emulsion, Alkali Soluable Resin (CAS# 25053-63-8)

CAUTION: HARMFUL IF SWALLOWED KEEP OUT OF REACH OF CHILDREN

FOR PROFESSIONAL USE ONLY
Refer to MSDS for further information.

ULTRA SHIELD PRODUCTS CORP. 1.888.604.3625